

PRODUCT - SAFETY DATA SHEET

(SDS)

Issued Date - Aug. 21, 2018

Revision Number: 1.20

Section 1. Product and Company Identification

Product Name: Reance[™] - Bonded Magnets Code: None

Product Type: Flexible Magnet Item #: Reance "F65B" **Restriction Use:** None Identified Region: **United States**

Contact Information:

Company Address: The Electrodyne Company

4188 Taylor Road

Batavia, Ohio 45103 USA

Telephone # 1-513-732-2822 Fax #: 1-513-732-6953

Web Site: www.edyne.com

Section 2. Hazard Identification

EMERGENCY OVERVIEW

This product when used under reasonable conditions and in accordance with the Electrodyne directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the production's directions for use may affect the performance of the product

Under standard conditions of use, this product is not expected to create any unusual emergency hazards.

This is a non-combustible, non-reactive solid material. Use methods as specified in Section 5. Fire-Fighting Measures suitable to fight surrounding fire.

Contact with the eve may result in unintentional rubbing irritation characterized by itching or redness.

Due to product form, exposures to dusts and fumes are not expected to occur.

NOTE: If this product is cut with power cutting equipment (such as saws, drilling, grinding or sanding equipment), dust generated may cause eye, skin, respiratory irritation and/or congestion in extreme cases. Prolonged and excessive skin contact may result in slight irritation. Use proper of safety and protection apparatus (Safety Glasses, Respiratory Equipment, etc.) is recommended when using power cutting equipment.

Hazard Class	Hazard Category
Skin Irritation:	0
Eye Irritation:	0
Inhalation:	0
Ingestion:	0

GHS Pictogram

Hazard Statement:



Warning - Material that is magnetized "Only" - Individuals with pacemakers, other medical electronic devices or metallic implants, magnetized material may affect operation of the device, do not handle, seek medical advice.

Note: * When cutting, sanding, grinding or drilling of this product, fine powder and/or particulates may ignite at room temperature in air.

GHS Ratings: Health: 0 Fire: 4 Physical Hazard: 0

Hazard Scale: 5 = Minimal Hazard 4 = Slight Hazard 3 = Moderate Hazard 2 = Serious Hazard 1 = Severe Hazard

Precautionary Statements

Skin: This product may produce skin abrasions. Prevention: Avoid mechanical rubbing as it may increase skin irritation. Wash thoroughly after handling. Wash exposed skin with soap and water. If irritation develops or persists, Response: seek medical attention. Particulates from this product may cause slight irritation or discomfort of the eye from cutting, sanding, Eye: grinding or drilling of this product. Prevention: Avoid unintentional scratching or rubbing irritation of the eye, could result in permanent cornea damage. Rinse/Flush eyes cautiously with copious/large amounts of water for 5-15 minutes while holding eyelids open. Response: Remove contact lenses, if present and easy to remove. If eye irritation persists, get medical attention.

Precautionary Stateme	nts (Continued)
Inhalation:	Inhalation of dusts produced during cutting, drilling, grinding or sanding of this product may cause irritation of the respiratory tract.
Prevention:	Avoid inhalation/breathing dust when cutting, drilling, grinding or sanding of this product. Use only in well-ventilated area.
Response:	If inhaled, remove person to fresh non-contaminated air, if breathing is difficult. Keep the person comfortable for breathing. If not breathing, give artificial respiration, preferably mouth to mouth. (CPR). Get medical attention immediately.
Ingestion: Prevention: Response:	Product is not intended to be ingested or eaten. Not a likely route of entry. Do not eat or ingest this product. If the product is ingested, do not induce vomiting. Seek medical attention, immediately.
Product Storage:	Protect material against physical damage. Product should be kept dry and be protected from the elements. Store material at room temperature - normal conditions and should be kept out of direct sunlight. Warehouse storage should be in accordance with package directions, if any.
Disposal	Dispose of content and/or container in accordance with Federal, State/Provincial, Local Governmental, Regional, National, and/or International Regulations requirements.
	Note: This product should not be burned as construction waste.

Classification complies with OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 12 for Ecological Information

Section 3. Composition/Information on Ingredients				
Ingredients (specific)	Formula:	%	CAS Number	Chemical Family
Neodymium	Nd	24.177	7440-00-8	Neodymium
Boron	В	0.827	7440-42-8	Boron
Cobalt	СО	4.596	7440-48-4	Cobalt
Iron	Fe	62.328	7439-89-6	Iron
Ethylene - Vinyl Acetate Copolymer	C ₆ H ₁₀ O ₂	3.134	24937-78-8	Synthetic Rubber
Vinyl Acetate Copolymer with Ethylene	C ₆ H ₁₀ O ₂	1.051	24937-78-8	Polyethylene Copolymer
Trade Secret	N/A	0.084 - 3.803	N/A	No SVHC Chemicals present

See Section 11 for Toxicological Information.		
	Section 4. First-Aid Measures	
Description of first aid measures		
Skin contact	 Avoid mechanical rubbing as it may increase skin irritation. Wash thoroughly after handling. Wash exposed skin with soap and water. If irritation develops or persists, seek medical attention. 	
Eye Contact	 Particulates from this product may cause slight irritation or discomfort of the eye from cutting, sanding, grinding or drilling of this product. Rinse/Flush eyes cautiously with copious/large amounts of water for 5-15 minutes while holding eyelids open. Remove contact lenses, if present and easy to remove. Continue to rinse. If eye irritation persists, get medical attention. 	
Inhalation	 Inhalation of dusts produced during cutting, drilling, grinding or sanding of this product may cause irritation of the respiratory tract. If inhaled, remove person to fresh non-contaminated air, if breathing is difficult. Keep the person comfortable for breathing. If not breathing, give artificial respiration, preferably mouth to mouth. (CPR). Get medical attention immediately. 	
Ingestion	 If the product is ingested, Do Not induce vomiting. If person is drowsy or unconscious and vomiting, place on the left side with head down. Seek medical attention, immediately. 	

See Section 2 for Potential Health Effects.

See Section 2 for Potential Health Effects.			
	Section 5. Fire-Fighting Measures		
Extinguisher Media:			
Suitable extinguishing media:	 Not applicable for solid magnets. <u>Do not use water H₂O, Carbon dioxide CO2 or Halogens if material is ignited</u>. Cover with Sand, or use Class D Fire Extinguishers such as Met-L-X or Na-X Fire Extinguishers. 		
Unsuitable extinguishing media:	 Do not use ABC Fire Extinguishers or use water H₂O, Carbon dioxide CO2 or Halogens if material is ignited. 		
Special fire fighting procedures:	 Note: When cutting, sanding, grinding or drilling of this product, fine powder/particulates may ignite at room temperature in air. Probably will react with water and release hydrogen slowly. For fine powder/particulates that have ignited, cover with sand, or use Class D Fire Extinguishers such as Met-L-X or Na-X Fire Extinguishers to extinguish the fire. 		
Unusual fire or explosion hazards:	Not Applicable for solid magnets.		
Hazardous combustion products:	 None known – for solid magnets. The decomposition products from this material are those that would be expected from any organic (carbon-containing) material, and are mainly derived from pyrolysis or burning of the polymer. 		
	Note: This product should not be burned as construction waste.		
Advice for firefighters:	 Promptly isolate the scene by removing all persons from the vicinity of the incident, if there is a fire. Wear appropriate protective equipment including respiratory protection as conditions warrant. 		
	 Special Fire Fighting Procedures - Not Necessary for solid magnets. Note: When cutting, sanding, grinding or drilling of this product, fine powder/particulates may ignite at room temperature in air. Probably will react with water and release hydrogen slowly. For fine powder/particulates that have ignited, cover with sand, or use Class D Fire Extinguishers such as Met-L-X or Na-X Fire Extinguishers to extinguish the fire. 		

Section 6 - Accidental Release Measures				
Use personal protection recommen	ded in Section 8 and emergency procedures			
Personal Precautions:	 Avoid breathing dust. when cutting, drilling, grinding or sanding of this product may cause irritation of the respiratory tract. Wear appropriate protective equipment including respiratory protection as conditions warrant. Provide adequate ventilation Wear appropriate respirator when ventilation is inadequate. 			
Evacuation & Special Procedure:	None necessary			
For emergency responders:	 Keep unauthorized personnel away. Avoid breathing dust. if product was processed by when cutting, drilling, grinding or sanding of this product. Wear appropriate protective equipment including respiratory protection as conditions warrant. Provide adequate ventilation Wear appropriate respirator when ventilation is inadequate. 			
Environmental precautions:	No Special handling. Material may be magnetized			
Clean-up methods:	 Sweep up or gather material and place in appropriate container for disposal. Note: This product should not be burned as construction waste. 			
	 Dispose of content and/or container in accordance with Federal, State/Provincial, Local Governmental, Regional, National, and/or International Regulations requirements. 			
	Note: This product should not be burned as construction waste.			

	Section 7. Handling and Storage
Precautions for safe handling	
Handling	 Use only with adequate ventilation. If product is being processed by cutting, grinding or sanding, avoid mechanical rubbing as it may increase skin irritation. Prevent contact with eyes. Do not breathe dust. Customary personal hygiene measures, such as washing hands after working with these products are recommended.

	Section 7. Handling and Storage - Continued	
Precautions for safe handling		
Conditions for safe storage, inc	luding any incompatibilities	
Protect material against physical damage. Product should be kept dry and be protected from the elements away from heat, sparks and open flame. Store material at room temperature - normal conditions and should be kept out of direct sunlight. Warehouse storage should be in accordance with package directions, if any.		
Incompatible Materials or Ignition Sources	 Keep away from heat, ignition sources, oxidizers and strong acids. 	

Section	on 8. Exposure Controls/Personal Protection
Exposure limit values:	Not Applicable
Engineering Measures/Controls	 No special protective control measures are necessary for use of this product. Under normal conditions, this material is not expected to release, or otherwise result in exposure to a hazardous chemical. Use only with adequate ventilation. If user operations generate dust, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. In case of insufficient ventilation, wear suitable respiratory equipment.
Respiratory Protection	 In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced
Eye/Face Protection	 Material in its natural state, protective equipment is not known to be necessary. If user operations require additional process manufacturing, use of Safety glasses with side-shields may be worn to reduce the risk of eye injury. Example: If this product is cut with power cutting equipment (such as saws, drilling, grinding or sanding equipment) or related activities wear safety goggles or safety glasses with side shields.
Hands	 Material in its natural state, protective equipment is not known to be necessary. Under normal conditions of use this product is not expected to cause skin irritation. If additional process manufacturing is required, to reduce the risk of skin irritation due to dust generated by power cutting equipment activities - leather or other appropriate work gloves are recommended.
Skin/Body ●	 Material in its natural state, protective equipment is not known to be necessary. Under normal conditions of use this product is not expected to cause skin irritation. If additional process manufacturing is required, to reduce the risk of skin irritation due to dust generated by power cutting equipment activities - leather or other appropriate work gloves and either an apron or lab coat are recommended.
Personal Protective Equipment (Pictograms)	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Type of equipment should be approved by a specialist before additional process manufacturing of this product.

Section 9. Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Metallic Grey, Dark Grey Flexible Magnet Material
Color	Metallic Grey, Dark Grey	Odor	Not Applicable - No Vapors
Taste	Not Available	Particulate Type	Not Relevant
Particulate Size	Not Relevant	Aerosol Type	Not Relevant – Not an Aerosol
Odor Threshold	Not Applicable - No Vapors	Physical & Chemical Properties	Not Available
General Properties			
Boiling Point (° C)	Not Applicable – Does Not Boil	Melting Point	Not Applicable – Does Not Melt
Freezing Point (° C)	Not Available	Decomposition Temperature	Not Available
Heat of Decomposition	Not Available	pH	Not Applicable
Specific Gravity/Relative Density	5.5		
Solubility in Water	Insoluble	Coefficient of Water/Oil Distribution	Reactivity in Water - None
Viscosity	Not Relevant	Explosive Properties	None
Oxidizing Properties	Not Relevant		
Volatility			
Vapor Pressure (mmHg)	Not Applicable - No Vapors	Vapor Density (air = 1)	Not Applicable - No Vapors
Evaporation Rate	Not Applicable - No Vapors	VOC (Wt.)	Not Applicable - No Vapors
Volatiles (Vol)	Not Applicable - No Vapors	, ,	
Flammability	· · · · · · · · · · · · · · · · · · ·		
Flash Point	Note: Cutting, sanding, grinding or drilling of this product, fine powder/particulates may ignite at room temperature in air. Probably will react with water and release hydrogen slowly.	Burning Time	Not Available
Burning Rate	Not Available	Auto ignition	Not Available
Flame duration	Not Available	Flame Height	Not Available
Ignition distance	Not Available	Flammability (Solid, Gas)	Not Available

Section 10.	Stability and	Reactivity
OCCUPII IO.	Otability and	a ixcactivity

Reactivity

Chemical stability

Possibility of hazardous reactions

Conditions to avoid

Incompatible materials

Hazardous decomposition products

- None Known As a solid. No dangerous reaction known under conditions of normal use.
- Stable under ordinary conditions of use, under normal temperatures, pressures and storage.
- None Expected Hazardous polymerization will not occur.
- High temperatures, sparks, open flames, other sources of ignition. Prevent Dust accumulation.
- None Known
- None Known Decomposition products from this material are those that would be expected from any organic (carbon-containing) material, and are mainly derived from pyrolysis or burning of the polymer.

These decomposition products may include carbon dioxide, carbon monoxide, carbon particles, Nitrogen oxides, Hydrocarbons.

Note: This product should not be burned as construction waste.

Section 11. Toxicological Information

Information on toxicological effects

Component Name	CAS	Data	
Reance TM " F65B " - Bonded Magnets Note: Material is a Solid	Not Listed	This product when used under reasonable conditions and in accordance with the Electrodyne directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the production's directions for use may affect the performance of the product.	
Route(s) of entry/exposure	 Inhalation, Skin, Eye, Ingestion – If this product is not used under reasonable conditions and in accordance with the Electrodyne directions for use. 		
Effects of Acute Exposure	None Known		
Effects of chronic exposure	None Known		
Irritancy of Product	None Known		
Skin sensitization	None Known		
Respiratory sensitization	None known s	ignificant effects or critical hazards.	
Carcinogenicity – IARC Monographs	None known significant effects or critical hazards.		
Carcinogenicity - ACGIH	No - Not Listed		
Reproductive toxicity	No - Not Listed		
Teratogenicity	No - Not Listed		
Embrotoxicity	No - Not Listed		
Mutagenicity	No - Not Listed		
Name of synergistic products/effects	None known significant effects or critical hazards.		
Other Toxic Effects on Humans	None known significant effects or critical hazards.		

Section 12. Ecological Information

Toxicity

Solubility in Water	Insoluble
Reactivity in Water	• None
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in Soil	No data available
Other adverse effects	 No studies have been found.
Other Information	 No data is available on the adverse effects of this material on the environment. Reactivity in Water – None

	Section 13. Disposal Considerations
Waste treatment methods	
Product waste	 Dispose of content and/or container in accordance with Federal, State/Provincial, Local Governmental, Regional, National, and/or International Regulations requirements. Note: This product should not be burned as construction
Packaging waste	 Dispose of content and/or container in accordance with Federal, State/Provincial, Local Governmental, Regional, National, and/or International Regulations requirements. Note: This product should not be burned as construction

Section 14. Transport Information

Special Shipping Information

Shipping Name This product is not classified as a hazardous material for transport	
Hazard Class None	Packaging Group None
Identification Number None	
TGS None	DOT None - Not Regulated - Not classified as a hazardous material for transport
IMO None	CAQ None

Section 15. Regulatory Information				
15.1 US Federal Regulations				
GHS Classification Note: * Material will smolder when preheated to 850°F (454° C) GHS Ratings: Health: 0 Fire: 4 Physical Hazard: 0 Hazard Scale: 5 = Minimal Hazard, 4 = Slight Hazard, 3 = Moderate Hazard, 2 = Serious Hazard, 1 = Severe Hazard				
<u>-</u>	s = Moderate Hazard, 2 = Serious Hazard, 1 = Severe Hazard			
<u>-</u>	s = Moderate Hazard, 2 = Serious Hazard, 1 = Severe Hazard WHMIS & NFPA			
Hazard Scale: 5 = Minimal Hazard, 4 = Slight Hazard, OSHA	· 			
Hazard Scale: 5 = Minimal Hazard, 4 = Slight Hazard, 3	WHMIS & NFPA			

Reference - Air Freight Shipments only - May be restricted as magnetized material. IATA (Class 9, Miscellaneous). Shipments of UN2807, Magnetized material field strength and identification (Labelled) which conform to IATA - Packing Instruction 953 can be shipped only to, from, and within certain countries. Refer to the IATA Dangerous Goods Regulations publication (you can get a copy of this documentation from your freight carrier or order it from IATA directly).

15.2 US State Regulations		
Ingredient – None Listed / Regulated for California Proposition 65		
US - California – Proposition 65 Carcinogens List	WARNING: None Listed	
US - California – Proposition 65 Reproductive Toxicity List – Female or /Male Only.	WARNING: None Listed	

Section 16. Other Information

Additional Information

Product Family: Plastalloy™ This SDS was prepared by The Electrodyne Company.

History:

Preparation Date: 28 May 2015
Issued Date: 28 May 2015
Last Revision Date: 21 August 2018

Version Number: 1.20

Section 16. Other Information – Notice to Reader Continued on Page 8

Section 16. Other Information – Notice to Reader Continued

Notice to Reader

Disclaimer: The data in this Material Safety Data Sheet relates only to the specific material designated herein. It does not relate to use in combination with any other material or in any process. This Safety Data Sheet (SDS) has been reviewed to fully comply with the guidance contained in the ANSI MSDS standard (ANSI Z400.1-2010) and Classification complies with OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. Final determination of suitability of any material is the sole responsibility of the user. This would include the Hazardous Statement in Section 2 Hazard Identification regarding to Warning – Material that is magnetized "Only" - Individuals with pacemakers, other medical electronic devices or metallic implants, magnetized material may affect the operation of the device, do not handle, seek medical advice. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. We make no representation as to completeness or accuracy. In no event we shall be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.

Manufacturer assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, manufacturer assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.

*** END OF SDS ***